OUALITY LIFTS

10K TWO-POST EQ10

Get the most out of your budget with the EQ10 Two-Post Lift. This lift features 3-Stage front and 2-Stage rear arms with automatic arm restraints for safe spotting, a single-point lock release system to disengage column locks simultaneously, a padded overhead shut-off bar to prevent vehicle damage, and a black textured powder coat finish for sleek, long-lasting durability.

REQUIREMENTS



HEIGHT: 12' MINIMUM



WIDTH: 14' RECOMMENDED



DEPTH: 24' RECOMMENDED



POWER: 208-230V, 1PH, 30A



CONCRETE

4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days

SPECIFICATIONS

MODEL NUMBER	EQ10
Lifting Capacity	10,000 lbs.
Configuration	Symmetric
Arms	3-Stage Front / 2-Stage Rear
Overall Height	143%"
Rise Height	721/4"
Pad Height	41⁄4"
Overall Width (C)	131¾"
Inside Columns (D)	1101/4"
Drive-Thru Clearance	983/8"
Floor to Overhead Switch	137"
Front Arm Reach (F)	21¾" - 39¼"
Rear Arm Reach (G)	38¾" - 55¾"
Motor / Voltage	2HP, 208-230v, 60Hz, 1Ph
Rise Time	44 s
Ceiling Height Required	12'
ALI® Certified	Yes
Color	Black

